


Code *EK-PWT-UN*



Description

2P+E 5/6/10/13A multi standard socket – shuttered
Adapt for plug: see Table

General Specification




- 2 modules
- Colour: Grey RAL7016 – Matt surface
- Isolating material: Polycarbonate for front cover and base
- Adapt all frames of Ekinex
- Screw type terminals up to 2,5 mm²
- Complying to IEC 60884-1:2002 + A1:2006 + A2:2013
- Safety shutters according to the standard
- Power devices: 10A 127Vac-250Vac
- RoHS compliant

Technical characteristics according to IEC standards

- electric strength: > 5MOhm
- withstand voltage: > 2000V
- resistance to the abnormal heat: 7 days @ 80°C
- resistance to fire (glow wire test) IEC 60695-2-11:
 - 850°C for insulating material retaining current-carrying parts;
 - 650°C for other parts.
- mechanical impact strength: IK04 according to IEC 62262
- storage temperature: -10°C to +60 °C
- operating temperature: -5°C to +45 °C

Dimensions (mm)



Suitable plugs	
Chinese plug 2P 10 A 250 V~	 
German plug 2P 16 A 250 V~ ("Schuko" type)	 
British plug 2P+T 5 A 250 V~	 
Europlug 2P 2.5 A 250 V~	 
Chinese plug 2P+T 10 A 250 V~ Australian plug 2P+T 10 A 250 V~	 
British plug 2P+T 13 A 250 V~	 